


# Data sheet

|                |  |
|----------------|--|
| ID             | <b>ASD 70</b>  |
| Description    | combined distribution and outlet box   |
| Properties     | alignable, with coupling system for aligning in standard distance of 71 mm and adjustable fixing of outlet devices, mounting screw spacing 60 mm |
| Colour         | black, similar to RAL 9005   |
| Classification | AC 400 V   |



Norms: ÖVE/ÖNORM EN 60670-1:2014, ÖVE/ÖNORM EN 60670-22:2007



Halogen free  
True

Degree of protection (IP)  
IP30

| Art. no. | Dimensions Ø/LxB x T | Small Package | Large Package |
|----------|----------------------|---------------|---------------|
| 020 912  | Ø 75 x 45 mm         | 100 pc        | 3500 pc       |

## Further technical details

| Details                      |          |
|------------------------------|----------|
| break-out opening            | True     |
| seal membrane                | False    |
| nozzle                       | False    |
| step membrane                | False    |
| Mounting switching equipment | Screwing |
| Luminaire hook mounting      | False    |
| Nozzle                       | None     |
| With nail lugs               | False    |
| Circuit integrity            | None     |

| Details                      |                         |
|------------------------------|-------------------------|
| Model                        | Single                  |
| Shape                        | Round                   |
| Mounting method              | Flush mounted (plaster) |
| With screws                  | False                   |
| Provided with revolving ring | False                   |
| Connectable                  | True                    |
| Equipped with                |                         |
| Cover attachment             | Snap on                 |
| Material                     | PS                      |