

Data sheet

Part No.

FXKVR BK

Description

double-walled ducting with draw-wire,
halogen-free, low smoke, LS0H
corrugated exterior, smooth interior, including one
coupler
medium resistance against compression, normal
impact resistance

Colour

black, similar to RAL 9005

Fire Behaviour

flame propagating

Classification


N 450

Compression
resistance

> 450 N



Standard: EN 61386-1, EN 61386-24, OVE E 8635 (ÖNORM E 6517)



Working temperature

-30 to +70 °C

Art. No.	ED	ID	Bending radius	PU	PU
055107	40 mm	31 mm	350 mm	50 m	1400 m
041925	50 mm	40 mm	350 mm	50 m	1200 m
032332	63 mm	50 mm	350 mm	50 m	-
026353	75 mm	61 mm	375 mm	50 m	-
041343	90 mm	74 mm	420 mm	50 m	-
041344	110 mm	92 mm	540 mm	50 m	-
041990	125 mm	105 mm	600 mm	50 m	-
042514	160 mm	136 mm	650 mm	25 m	-
099585	200 mm	176 mm	1000 mm	25 m	-

Areas of Recommended Application

Area

Flush mounted (plaster)	false
Surface mounted	false
Suitable for installation on wood	false
Hollow wall	false
Suitable for concrete installation	true
Machine and systems installation	false
Suitable for subsurface installation (screed)	true
Outdoor installation	false
Underground installation	true

Further technical details

Details

Model	Pliable
Shape	Outer side ribbed, inner side plain
Surface protection	Untreated
Material	PE-HD