



Data sheet

Part No.	HFX BK
Description	pliable insulation conduit with turbogrooves, halogen-free, corrugated
Properties	light compression resistance, medium impact resistance Dimension 20 and 25 with glide core
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	23332
Compression resistance	> 320 N



Standard: EN 61386-1, EN 61386-22, EN 60754, EN 50642, EN 61034, IEC 63355



Compressive strength class	Impact strength	Operating temperature	Bending strength
Light (Class 2)	Medium (class 3)	-15 to +105 °C	Pliable

Art. No.	ED	ID	Bending radius	PU	PU
102302	16 mm	10 mm	64 mm	100 m	4000 m
106057	20 mm	14 mm	80 mm	100 m	4000 m
106058	25 mm	18 mm	100 mm	100 m	2800 m
102305	32 mm	24 mm	128 mm	50 m	1000 m
102306	40 mm	30 mm	160 mm	25 m	500 m
102307	50 mm	39 mm	200 mm	25 m	300 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	true
Surface mounted	true
Suitable for concrete installation	false
Machine and systems installation	false
Suitable for subsurface installation (screed)	false
Outdoor installation	false
Suitable for installation on wood	true
Hollow wall	true
Underground installation	false

Further technical details

Details	
Halogen free	true
With sleeve	false
Fire retardant version	true
Material	PP-Blend



Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.